



---

## 1500 ST Drydock - Built 2012

---

### PRODUCT DESCRIPTION

Built 2012 - Custom 1500 ST Reported Lifting Capacity  
Dimensions: 150' Long x 74' Wide x 6.5' deep Pontoon  
Hull - Drydock was constructed with outboard 26.5' tall x  
5' wide wing walls with a longitudinal distance of 180'  
and 65' measured distance transversely between the  
wing walls. The drydock was constructed with a  
centerline longitudinal bulkhead used to support a  
centerline keel blockage system with a 4' wide x 1" thick  
overlay plate in addition to three port and starboard  
watertight compartments separated by two transverse  
bulkheads. Pontoon Arrangement : Total of six  
watertight compartments segregated by two transverse  
and one longitudinal bulkhead with a centerline keel  
blockage system Electrical Power : The drydock is fitted  
with a Stamford 200-KW generator driven by a Cummins  
6-cylinder diesel engine with 480-volt shore power feed  
Floating/Submersible Drydock : The drydock is fitted  
with six Power Flow 8" diameter submersible and/or  
non-clogging vertical deep well pumps, each set in a  
sump powered by a 25-HP electric motor. The drydock is  
also constructed with 8" diameter discharge and  
flooding valves and 12" diameter vertical vent stacks.  
The drydock is constructed with an air actuator system  
atop each discharge valve and a reach rod with manual  
valves for flooding.

**Categories:** [Shipyard & Marina Equipment](#)

**Condition** RTO

**Additional Information** Full Survey available from End  
2019.

---



