



195' PRODUCTION BARGE

PRODUCT DESCRIPTION

195' PRODUCTION BARG

195' x 35' x 12'

Bulkheads 5/16"

10-Deck longitudinal angles 5" x 3" x 5/16".

10-Bottom longitudinal angles 6" x 3.5" x 5/16".

4-Side longitudinal angles 5" x 3.5" x 5/16"

10-Aft bulkhead vertical angles 5" x 3.5" x 5/16"

8-Bulkhead gussets 16" x 5/16" x 16" (forward and aft)

10-Bulkhead gussets upper 12" x 3/8" x 1' (forward and aft)

10-Bulkhead gussets lower 12" x 3/8" x 1' (forward and aft)

7-Truss frames were construction out of the following:

NOTE: Truss frames are set 5' aft the forward bulkhead and set 5' apart thereafter.

Overhead transverse deck girder 8" @ 11.5 lbs. channel

Lower transverse deck girder 12" @ 20.7 lbs. channel

Outboard girders 10" 15.3lb channel

Inboard girders 5" x 3" x 5/16"

3-Vertical stiffeners 5" x 5" x 5/16" angle

4-Diagonal stiffeners 3" x 3" x 5/16" angle

1-Longitudinal diagonal angle 6" x 5/16" x 6" angles



Categories: [Barges](#)

