



220 Ft. Offshore Supply Vessel - Built 2000

PRODUCT DESCRIPTION

DIMENSIONS

Length: 220 ft 0 in (67.1 m) Beam: 46 ft 0 in (14.0 m)

Draft Max: 13 ft 8 in (4.17 m). Draft Min: 9 ft 0 in (2.74 m)

Gross: 1,255 GT Net : 376 NT

Certifications: Oceans, SIP, USCG Subchapter L

Classifications: American Bureau of Shipping, Loadline



PERFORMANCE

Max Speed: 12.0 kts 215 gal/hr (814 l/hr)

Cruise Speed: 10.0 kts 120 gal/hr (454 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines: 2 x Cummins QSK60 Total
Horsepower: 4,000 hp

Propellers: FPP, 4-Blade Propeller Diameter: 96in
(2,438mm)

Primary Generators: 2 x Cummins NT855
Total Rating: 250 kW

Power Generation: 480V/60 Hz/3-Phase





*Bow Thruster: 1 x SMI FPP Tunnel
Total Horsepower: 755 hp*

*Stern Thruster: 1 x SMI FPP Tunnel
Total Horsepower: 525 hp*

Rudder: Independent Steering, Spade Type

CAPACITIES AND DELIVERY RATES

Deadweight: 1,630 LT (1,656 MT)

Deck Area: 138ft x 38ft (5,244ft²)

42.1m x 11.6m (487.2m²)

Deck Cargo: 1,025 LT (1,041 MT)

Deck Load Rating: 540 lbs/ft² (3 MT/m²)

Dry Bulk: 8,135 ft³ (230 m³)



System Pressure: 80 psi (5.5 bar)

*Brine: 3,050 bbl (485 m³) Discharge Rate: 1,200
GPM (273 m³/hr)*

*Liquid Mud: 3,050 bbl (485 m³) Discharge Rate: 1,200
GPM (273 m³/hr)*

Potable Water: 27,850 gal (105 m³)

*Rig Fuel: 112,030 gal (424 m³) Discharge Rate: 380
GPM (86 m³/hr)*

*Rig Water: 100,250 gal (379 m³) Discharge Rate: 400 GPM
(91 m³/hr)*

*Cooler Area: 450 ft² (13 m²) Freezer Area: 375 ft²
(11 m²)*

Off Ship Firefighting Monitors: 1



Total Flow Rate: 2,400 gal/min (546 m³/hr)

ELECTRONICS

Auto Pilot, Beier IVCS 2000, C-Nav, CCTV Cameras, Depth Sounder, DGPS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick

Control, Loudhailer, Mag Compass, MAMS/VMS, Navtex, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band

Radar

ACCOMMODATIONS

10 air conditioned/heated staterooms certified for 22 person berthing.

DP1



Categories: [Supply Boats](#)

Engine Manufacturer/Brand Cummins

Engine Model QSK60

HP 4000

Generator Manufacturer/Brand Cummins

Generator Model NT855

kW Rating 250

Voltage 3 phase - 480 volt

Condition Used

