



Multiple BROHL 250kN Mooring Winches - Never Used

PRODUCT DESCRIPTION

Five BROHL 250kN Mooring Winches Available - Never Used

Specifications:

Line Pull 1st Layer: 250 kN

Line Speed 1st Layer: 5,8 m/min / 11,7 m/min

Line Pull 10th Layer: 119 kN

Line Speed 10th Layer: 12,2 m/min / 24,6 m/min.

Brake holding force:

Band Brake 1st Layer: 600 kN

Brake Holding Torque: 174 kNm

Electromagnetic Brake 1st Layer: 600 kN

Rope: Steel Rope 38 mm Ø

Drum Dimensions: Ø 580/1690 x 1080 lg.

Storage Capacity: 775 m in 10 layers

Drive:





Three-Phase Squirrel Cage Motor

Type: KDKF200L-8/4/TF/ST/OD/BR

Rated Voltage (see E-part): 480 V AC 3ph 60 Hz

Power: 27 kW / 27 kW

Speed: 870 rpm / 1760 rpm

Poles: 8 / 4

Cooling: Surface Cooled

Build in Electromagnetic Brake: SFB 63/ 630 Nm

Voltage: 110 V D.C.

Gear:

Gear Ratio: 287:1

Oil Contents: Approx. 85 ltr.



Categories: [Winches](#)

Winch Manufacturer / Brand BROHL

Number of Drums 1

Condition Surplus

Additional Information Operations and Maintenance

Manual Is Available. Some Images Come From
Operations and Maintenance Manual.



