



## **New Build Truckable Tug**

## PRODUCT DESCRIPTION

LOA: 25'-10" Beam:13'-6" Draft:4'

Twin Cummins 6.7L-305hp
(2) TwinDisc Gears, 3:1 Ratio
Single PTO drive
Two (2) 34" Props2 1/2" Aquamet Shafts
Dripless Prop Shaft Seals

Hull Structure:

5/16" Hull Plating 5/16" Fwd & Aft Watertight Bulkheads 5/16" Bulwarks 2 1/2" Rudder Shaft Crest Aquamet Stainless Engine Room Louvers

Five (5) Anodes

Pilot House:

15-18 ft Lifting Eye (Crane) Height Sliding Vent Windows LED Dome Light

Additional Outfitting: Independent 12V Breaker Panel 12V Tow Lights 12V Anchor Lights

Total over the road weight with 100 gallons of fuel and optional pilot house extension is 37,200 lbs with the standard Cummins engines or 38,640 lbs with the optional CAT engines.







**Categories:** Pushboats

Additional Information Engine Room: 700 Gallon Fuel Capacity 12V Rule Bilge Pump System Keel Cooled Engines Dry Exhaust System (SS) Separate Battery Systems Ahead bollard thrust rating of over 4 tons Deck Equipment: Four (4) Side "H" Bits, 3" Bow and Stern "H" Bits 8 Ft. Push Knees Four (4) Steel Lifting Eyes, 1" 12V Deck or Running Lights Pilot House: Fold Down Mast Dometic Electric Power Steering Electronic Throttle Controls Standard Horizon Marine VHFVHF Antenna mount 12V Dash Outlet Circulating Wheelhouse Fan Optional Equipment Upgrades Two (2) Caterpillar C7.1 "C" Rated 355HP @ 2,500rpm Gallon Water Storage Tank Two (2) Deck Cable Winches. Deck Wash Down. USCG Life Savings Equipment Added Tire Fendering (3 sets of 3 per side)\*\*Other fendering options available upon request Upgraded EDGE Propeller (increases avg thrust by 18%) Aluminum Trunk extension HD Radar/ Depth Finder with Thru-Hull Transducer Roof Mount Air Conditioning Upgraded Marine Door (Weather Tight) H#Versatile Configuration: Use with Standard Pilot House or with Pilot House and Trunk Extension Est. Build Duration: 4 months





