New Construction Truckable Tug

PRODUCT DESCRIPTION

“25' 8" X 14 X 5
Draft 3’6” Approx.

Steel - All materials are domestic
Paint - All materials are white blasted with a 3 coat International Paint System or equivalent
Plating - Deck, sides = ¼ .bottom, bow and stem 5/16" thick. Corners 3/8”
Framing Spacing 0 – 13 = 1’8” & 13 – 15 = 2’
Hydraulic Steering -2 pumps, 5 gpm per engine, 1 driven off each main engine
Stuffing Boxes- PSS shaft seals
Push Knees - extended 6’1” above deck line.
Spot light- 1 (one) 12 volt DC mounted on pilot house
Running lights - Perce Navigation lights 12 volt DC
Bual works- 16" above deck line/ wrapped around entire haul with 2” flat top
Deck Hatches-1 hatch for each bow and stem void on deck flush mount
Horn - Fiamm/ Signaltone Airtone stainless steel 12 volt DC
VHF
GPS-Chart Plotter
Loud Hailer
Propellers 4 bronze work horse style 34 X 18
Main Engine Propeller shafts - 3 Aqua Met 17 S/S
Fuse Panels - 1 Bluesea Vertical waterproof fuse panel 12 volt DC
Fuel - 750 gallon capacity tank
Winches -nibrico manual 40 ton capacity
Windows - 100% glass custom fitted with optional tint

Throttle controls Cable style mechanical over electrical
Engine Room Blowers- 2 Jabsco 250 CFM 12 volt DC
Pilot Chair-Garelick Eez- in white deluxe pilot chair
Main engines -Cummins 6.7 L 305 HP @2600 rpm Gear
Twin disc 2.88: 1 reduction
Lube Oil 85 Gal
Trim Water 2,040 Gal
Hydraulic Oil 85 Gal
2 flanking Rudders SS 3” shafts

Categories: Tugboats
Additional Information One year craftsman warranty. All other warranties for equipment are manufacturer specific.