



Skagit model HPW-600 winch - Hydraulic

PRODUCT DESCRIPTION

Year of manufacture: OCT. 2013 WINCH RATINGS:
DRUM- GROOVED FOR Ø 3.00 Inch [Ø 76.2 mm] WIRE
ROPE. CAPACITY- 2,500 FEET [780 METERS] IN 7
LAYERS. LINE PULL- 385,700 LBS [175 MT] ON ALL
LAYERS @ 16.4 FEET PER MINUTE [5 METERS PER
MINUTE] BRAKE HOLDING- 694,500 LBS [315 mT] ON
ALL LAYERS. WEIGHT OF WIRE ROPE (INCLUDED IN
TOTAL WEIGHT) IS 48,000 LBS [21.8 MT]

Categories: [Winches](#)

Condition RTO

Additional Information From manual: 2.1 WINCH &
STORAGE REEL CAPACITY AND PERFORMANCE 2.1.1
WINCH STORAGE REEL Wire Rope Size: 76mm [3 inch]
76mm [3 inch] Barrel Diameter: 1524 mm [60 inch]
1524 mm [60 inch] Flange Diameter: 2743 mm [108
inch] 3048 mm [120 inch] Barrel Length: 1473 mm [58
inch] 1727 mm [68 inch] Wire Rope Capacity: 760 M
[2500 feet] 760 M [2500 feet] Winch Low Speed Winch
High Speed Reel Single Speed Rated Line Pull: 175 MT
50 MT 17 MT All Layers - [385,700 lbs] [110,000 lbs]
[37,500 lbs] Rated Speed: 5 m/min 17 m/min 17 m/min
All Layers - [16.4 fpm] [55.8 fpm] [55.8 fpm]
Dimensions: 32 ft L from Side, 17 ft-7 in L from Center
to Corner, (Approx 18 ft H) Total size (footprint) is
about Ø10 m circular including the rotary foundation.
Weight: 145 Te (318.778 lbs) including the rotary
foundation. The winch with rotary foundation can be
lifted as one piece including wire on the drum for quick
mobilization to the vessel. The winch unit can be
dismantled from the rotary foundation and sold
separately. Other appliCAtion could be subsea
hoisting winch with an A-frame, slip winch for a ship
yard, tug boat winch, pulling winch for bridge





construction etc. The original HPU is not included (was kept by Chevron), but we might have some alternative HPU's available depending on the pull and lifting speed required.

