



Slickline Unit Double Drum Powerpack



PRODUCT DESCRIPTION

Slickline Unit Double Drum Powerpack Engine Detroit 160HP, Air Rig Safe

Power Pack:

Power source is on a single chassis equipped with four (4) adjustable jacks and four (4) castor wheels. The whole load is Heli- portable, with four (4) legged slings maximum weight including hydraulic oil and diesel oil not to be more than 3,000 lbs.

Specification :

Diesel engine, 160 HP.
Rig Safe



Reel Pack :

First Drum Specifications:

Gear box for (4) speeds c/w double key way on the shaft and also in coupling and adjoining shaft.

It has a maximum line speed of: 2,200 feet per minute at surface 900 feet per minute at 20,000 feet.

It has a maximum line pull of:

4,000 lbs. at surface

9,000 lbs. at 20,000 feet.

The power pack and reel pack contains the following features: Engine oil temperature

Engine oil pressure:

Engine RPM's (to also monitor the engine time) Throttle

Hydraulic oil temperature Hydraulic oil pressure

Second Drum Specification :



Gear box for (4) speeds c/w double key way on the shaft and also in coupling and adjoining shaft.

The diameter of the reel core is not less than 9". The sides of drum are mounted to the core by threads (no welding).

It has a maximum line speed of: 3,800 feet per minute at surface 2,000 feet per minute at 18,000 feet.

It has a maximum line pull of 5,000 lbs. at 18,000 feet.

The power pack and reel pack contains the following features:

Engine oil temperature

Engine oil pressure

Engine RPM's (to also monitor the engine time) Throttle

Hydraulic oil temperature Hydraulic oil pressure

Accessory Equipment

Martin Decker weight indicator 0-6,000 lbs. on the operator console complete with 100 feet of hose and connection to connect a Martin Decker weight indicator.

Counter Head Assembly (feet) for both.

Veeder Root Counter Assembly (feet) and mounted on the operating console

Categories: [Marine Equipment & Parts](#), [Shipyard & Marina Equipment](#)

