

## NOTES

- 1. UNIT Z-8957 SHOWN WITH PROPOSED REWORKED TOP BEAM ON CUSTOMER PIERS
- 2. UNIT CAPACITY WITH PROPOSED REWORKED TOP BEAM INSTALLED: 440,000 LBS (200MT)
- 3. UNIT CAPACITY ASSUMES STRUCTURE IS IN GOOD AS SOLD CONDITION AND REQUIRES SERVICE INSPECTION
- 4. TOP BEAM REQUIRES RE-WORK FOR THE ADDITION OF FLANGES
- 5. PROPOSED TOP BEAM REWORK BASED ON CURRENT ICW OF 34'-0" (CUSTOMER TO CONFIRM)
- 6. SHOWN WITH (8) 10" X 56' NYLON 4-PLY SLING SETS
- 7. FOR RECOMMENDED PIER INFORMATION CONSULT OUR LAUNCHING PIERS DATA SHEET
- 8. CURRENT STEERING OK

ALL DIMENSIONS ARE NOMINAL PARINE TRAVELIFT В SHUTTLELIFT THIS DOCUMENT AND THE INFORMATION CONTAINED ROJECT NUMBER LATEST REVISION DESCRIPTION DATE NAME 109-0204 INITIAL RELEASE HEREIN IS THE PROPERTY OF DRAWN TWK 1/28/2022 MARINE TRAVELIFT INC. AND BOATHOIST - 200BFM SHALL NOTBE DISCLOSED OR
USED BY A RECIPIENT EXCEPTAS

GENERAL ARRANGEMENT REVISED 1/28/2022 SPECIFICALLY AUTHORIZED BY APPROVED MARINE TRAVELIET INC. Z-8957

CUSTOMER SIGNATURE PRINTED NAME DATE

DEALER SIGNATURE PRINTED NAME

DEALER SIGNATURE PRINTED NAME

DATE

DATE

DATE

THIS DOCUMENT MAY CONTAIN CONFIDENTIAL, PRIVILEGED OR PROPRIETARY INFORMATION AND IS INTENDED SOLEY FOR THE USE OF THE INDIVIDUAL, GROUP OR ENTITY TO WHOM IT IS ADDRESSED AND MUST NOT BE SHARED WITH THIRD PARTIES WITHOUT THE WRITTEN CONSENT OF MARINE TRAVELIET INC, THE CONTENT OF THIS DOCUMENT IS FOR INFORMATIONAL PURPOSES ONLY AND DOES NOT REPRESENT A CONTRACT OR ENGAGEMENT OF ANY SORT, IF YOU ARE NOT THE INTENDED RECIPIENT YOU ARE NOTIFIED THAT DISCLOSING, COPYING, DISTRIBUTING OR TAKING ANY ACTION IN RELIANCE ON THE CONTENTS OF THIS INFORMATION IS STRICTLY PROHIBITED.

